



- 1、Design Pressure 1.0MPa(10KG)
- 2、Design Temperature 66°C(150°F)
- 3、Min Temperature -10°C(14°F)
- 4、Media:Water PH3-10
- 5、Please operate it according to operation manual

- 1、设计压力1.0MPa(10KG)
- 2、设计温度66°C(150°F)
- 3、最低允许温度-10°C(14°F)
- 4、工作介质为PH3-10的水
- 5、请按照说明书正确使用

壳体型号 Model NO.	L (MM)	S (MM)	重量 Weight (KG)
GL80-150-20	789	300	18
GL80-150-40	1297	600	21
GL80-150-60	1805	1105	25

序号 NO.	名称 Name	材料 Material	数量 QTY	备注 Remarks
1	壳体 shell	环氧+玻璃钢 epoxy+glass fiber	1	
2	挡圈 retaining ring	SUS304	2	
3	进水端板 inlet sealing plate	A B S	1	
4	止推环 thrust cone	A B S	1	
5	密封圈 sealing ring	EPDM	4	
6	出水端板 outlet sealing plate	A B S	1	
7	捆带 strap	SUS304 +Rubber	2	
8	捆带螺栓 strap nut	SUS304	4	M8 × 90
9	鞍座 saddle	Nature Rubber	2	

SIGNATURE			河北成达管业有限公司 HEBEI CHENGDA PIPES CO., LTD		
	NAME	DATE			
DESIGN	陈勇	2018.10.8	比例 SCALE	材料 MATERIAL	型号 TYPE GL-80E-150P
REVIEW			数量 QUANTITY	光洁度 SMOOTH	描述 DESCRIPTION MEMBRANE HOUSING
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			投影 PROJ	电脑编号 NO.	图号 DRAWING NO. AWY-Z-01
			DO NOT MEASURE THE DIMENSIONS.		