



- 设计压力3.1MPa(450PSI)  
Design Pressure 3.1MPa(450PSI)
- 设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水  
Media:Water PH3-10
- 项目10仅在原水端; 项目5仅在浓水端;  
Item 10 is at the RAW end only; item 5 is at the concentrated end only; item 3 is at the conventional 1.5 inch.
- 请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	715	1435	1120	30
2	1731	2453	2136	37
3	2747	3469	3152	44
4	3763	4485	4168	51
5	4779	5501	5184	58
6	5795	6517	6200	65
7	6811	7533	7216	72

17	卡簧 PERMEATE RETAINING RING	2	SUS304
15/16	钢带STRAP+螺丝screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
14	鞍座SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
13	挡块螺丝 BAFFLE FIXING BOLTS	6	SUS304
12	挡块 LINK STOPPER	6	SUS304
11	承压头 (450Psi) HEAD SEAL	2	ABS
10	适配器ADAPTOR	2	ABS
08/09	适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM512+硅胶
07	π型密封胶圈 π SEALING RUBBER RING	2	硅胶
06	承载板BEARING PLATE	2	铸铝
05	止推环THRUST CONE	1	工程塑料Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口SIDE PORT	2	SUS304
02	侧口密封胶圈SIDE PORT SEAL RING	4	EPDM 512
01	壳体SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

	NAME	DATE
设计	陈勇	2020.1.8
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

河北成达华膜科技有限公司  
 Hebei Chengda Hualuo Technology Co., Ltd

型号 TYPE	单位UNIT:
80S300	MM

仅供参考, 零部件以图纸为准, 变更不另行通知