



10	Clean Water Plug	1	Engineering Plastic	
9	Hoop Bolt	4	SUS304	
8	Strap Bolt	4	SUS304	M8*70
7	Sadles	2	Soft PVC	
6	Plastic Strapping	2	Engineering Plastic	
5	Seal Plate Small O-ring	2	EPDM	19*2.65
4	Seal Plate Large O-ring	2	Silica gel	100*6
3	Sealing Plate	2	ABS	
2	Embrace Hoop	4	SUS304	
1	Shell Body	1	FRP	
S/N	Item	QTY	Material	Remarks

Length	L (mm)	S (mm)	Weight (kg)
1	1060	500	4
2	2076	1500	7

Technical Requirements:

1. The maximum pressure of Membrane Shell is: 300 PSI (2.1 MPA) ;
2. Working medium temperature:-10 ° C ~ 49 ° C;
3. The working medium is used for brackish water or seawater, Ph: 3 ~ 11

	NAME	DATE	Winder - G Hebei Chengda HuaMoTechnology	
DESIGN	Chen Yong	2021.08.15		
CHECK				
APPROVE				
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			TYPE	UNIT
			4" quick opening FRP membrane housing	MM
			For reference only, the parts shall be subject to the drawings without notice.	