



**警告!**

淡水口内部压力必须不超过  
120PSI (0.84Mpa)  
淡水出水口F---1"BSPP内螺纹  
Internal pressure must not  
exceed 120PSI (0.84Mpa)  
Fresh water outlet  
F---BSPP 1" internal  
thread

- 设计压力2.1MPa(300PSI)  
Design Pressure 2.1MPa(300PSI)
- 设计温度66℃ (150°F)  
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14°F)  
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水  
Media:Water PH3-10
- 图纸仅供参考, 具体以实物为准  
Drawings are for reference only, in kind
- 请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S Inch (mm)	L Inch (mm)	P Inch (mm)	重量 WEIGHT lb (kg)
1	735	1435	1120	25
2	1751	2451	2136	33
3	2767	3467	3152	41
4	3783	4483	4168	49
5	4799	5499	5184	57
6	5815	6515	6200	65
7	6831	7531	7216	73
8	7847	8547	8232	81

17	卡簧	PERMEATE RETAINING RING	2	SUS304
15/16	钢带	STRAP+螺丝screwhead	2-3	A-666,304+SUS304
14	鞍座	SADDLE	2-3	TPU(S60D)
13	挡块	BAFFLE FIXING BOLTS	6	SUS304
12	挡块	LINK STOPPER	6	SUS304
11	承压头	(450Psi)HEAD SEAL	2	ABS
10	适配器	ADAPTOR	2	ABS
09	适配器	O型圈ADAPTOR O RING	4	EPDM 512
07/08	承压头	O型圈HEAD SEAL O RING	2+4	EPDM 512
06	承载板	BEARING PLATE	1	SB-209,6061-T651
05	止推环	THRUST CONE	1	工程塑料Engineering Plastic
04	侧口	两圈SIDE DORT	2	SUS304
03	侧口	SIDE PORT	2	SUS304
02	侧口	密封圈SIDE PORT SEAL RING	4	EPDM 512
01	壳体	SHELL	1	FIBER GLASS +EPOXY
	名称		数量	材料

SIGNATURE			ROHONE 河北成达管业有限公司 HEBEI CHENGDA PIPES CO.,LTD		
	NAME	DATE	系列	材料 MATERIAL	型号 TYPE
DESIGN	陈勇	2018.10	比例 SCALE		A80S450P
REVIEW			数量 QUANTITY	光洁度 SMOOTH	描述 DESCRIPTION
					MEMBRANE HOUSING
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			投影 PROJ	电脑编号 NO.	图号 DRAWING NO.
					AWY-Z-01
DO NOT MEASURE THE DIMENSIONS.				单位UNIT:MM	