



- 设计压力6.9MPa(1000PSI)
Design Pressure 6.9MPa(1000PSI)
- 设计温度66°C (150° F)
Design Temperature 66°C (150° F)
- 最低允许温度-10°C (14° F)
Min Temperature -10°C (14° F)
- 工作介质为PH3-10的水
Media:Water PH3-10
- 净水口压力为0.88MPa (125PSI)
0.88MPa (125PSI)
- 项目3数量由客户选择决定; 项目5仅在浓水端
Media:Water PH3-10
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	430 (16.9)	1544 (60.8)	1147 (45.2)	66 (145)
2	1446 (56.9)	2560 (100.8)	2136 (85.2)	85 (187)
3	2462 (96.9)	3576 (140.8)	3152 (125.2)	104 (229)
4	3478 (136.9)	4592 (180.8)	4168 (165.2)	123 (270.6)
5	4494 (176.9)	5608 (220.8)	5184 (205.2)	142 (312)
6	5510 (216.9)	6624 (260.8)	6200 (245.2)	161 (354)
7	6526 (256.9)	7640 (300.8)	7216 (285.2)	180 (396)

18	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
17	螺栓 BOLT	6	SUS304
16	定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
15	挡块 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
14	嵌入钢圈 EMBEDDED RING	2	SUS304
12/13	钢带 STRAP+螺丝 screwhead	2-3	A-666, 304+SUS304
11	鞍座 SADDLE	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器O型圈 ADAPTOR O RING	4	EPDM 512
07	O型圈 O RING	4	EPDM 512
06	承载板 BEARING PLATE	1	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	SUS304
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

原浓水口规格	D	H
1. 5" (DN40)	280	165
2" (DN50)	280	165
2. 5" (DN65)	300	178

SIGNATURE		
NAME	DATE	
DESIGN	陈勇	2019.1.31
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder 河北成达管业有限公司 HEBEI CHENGDA PIPES CO., LTD	
型号 TYPE W80S1200	单位 UNIT: MM
仅供参考, 零部件以图纸为准, 变更不另行通知	