



技术要求:

1. 膜壳最大压力为: 300PSI (21KG/CM²);
2. 水介质温度: 1℃~49℃;
3. 不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 300PSI, (21KG/CM²)

Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

				9	鞍座Saddle	2-3	TPU(S60D)
				8	月牙片Crescent film	4	SA-213, 304
				7	钢带Steel strip	2-3	A666, 304
				6	钢带螺母Steel strip nut	4-6	HPB59-1
				5	大密封圈Large sealing ring	2	EPDM
				4	承压头O型圈Pressure head O type ring	2	EPDM
				3	钢带护套Steel sheath	2-3	软质PVC Soft PVC
				2	承压头Pressure head	2	ABS
				1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
长度编码 Length Code	L Inch (mm)	S Span (mm)	壳体重量 lb (kg)	序号	名称	数量	材料
40/14	19 (475)	6 (155)	6.2 (2.8)				
40/21	26 (653)	11 (300)	7.7 (3.5)				
2	85 (2151)	61 (1551)	17.4 (7.9)				
1	45 (1135)	23 (600)	10.8 (4.9)				

	NAME	DATE	Winder®-G 河北成达华膜科技有限公司 Hebei Chengda HuaMoTechnology Co., Ltd	
设计	陈勇	2019.4.19	型号 TYPE	单位UNIT:
审核			40E300	MM
审批			仅供参考, 零部件以图纸为准, 变更不另行通知	
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY				