



- 1、设计压力3.1MPa(450PSI)
Design Pressure 3.1MPa(450PSI)
- 2、设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、项目10仅在原水端；项目5仅在浓水端；
项目3为常规1.5寸。
Item 10 is at the RAW end only; item 5 is at the concentrated end only; item 3 is at the conventional 1.5 inch.
- 6、请按照说明书正确使用
Please operate it according to operation manual

| 长度编码 Length | S (mm) | L (mm) | P (mm) | 重量 WEIGHT (kg) | | | | |
|----------------|-----------|-----------|-----------|----------------------|-------|-------------------------------------|-----|-------------------------|
| 1 | 715 | 1435 | 1120 | 36 | 17 | 卡箍 PERMEATE RETAINING RING | 2 | SUS304 |
| 2 | 1731 | 2453 | 2136 | 45 | 15/16 | 钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90) | 2-3 | A-666, 304+A216 |
| 3 | 2747 | 3469 | 3152 | 54 | 14 | 鞍座SADDLE (3芯以上均为3个) | 2-3 | TPU(S60D) |
| 4 | 3763 | 4485 | 4168 | 63 | 13 | 挡块螺丝 BAFFLE FIXING BOLTS | 6 | SUS304 |
| 5 | 4779 | 5501 | 5184 | 72 | 12 | 挡块 LINK STOPPER | 6 | 铝合金 |
| 6 | 5795 | 6517 | 6200 | 81 | 11 | 承压头(450Psi) HEAD SEAL | 2 | ABS |
| 7 | 6811 | 7533 | 7216 | 90 | 10 | 适配器ADAPTOR | 2 | ABS |
| | | | | | 08/09 | 适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUE | 4+4 | EPDM512+硅胶 |
| | | | | | 07 | π型密封胶圈 π SEALING RUBBER RING | 2 | 硅胶 |
| | | | | | 06 | 承载板BEARING PLATE | 2 | 铸铝 |
| | | | | | 05 | 止推环THRUST CONE | 1 | 工程塑料Engineering Plastic |
| | | | | | 04 | 侧口两圈 SIDE DORT | 2 | SUS304 |
| | | | | | 03 | 侧口SIDE PORT | 2 | SUS304 |
| | | | | | 02 | 侧口密封胶圈SIDE PORT SEAL RING | 4 | EPDM 512 |
| | | | | | 01 | 壳体SHELL | 1 | FIBER GLASS +EPOXY |
| | | | | | | 名称 | 数量 | 材料 |

| | NAME | DATE | Winder-G 河北成达华膜科技有限公司 Hebei Chengda Huamo Technology Co., Ltd | |
|--|------|----------|---|---------|
| 设计 | 陈勇 | 2020.1.8 | 型号 TYPE | 单位UNIT: |
| 审核 | | | 80S450 | MM |
| 审批 | | | 仅供参考，零部件以图纸为准，变更不另行通知 | |
| THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY | | | | |