



- 1、设计压力8.3MPa(1200PSI)  
Design Pressure 8.3MPa(1200PSI)
- 2、设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水  
Media:Water PH3-10
- 5、图纸仅供参考，具体以实物为准  
Drawings are for reference only, in kind
- 6、请按照说明书正确使用  
Please operate it according to operation manual

长度编号 length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	800 (31.5)	1194 (47)	15.5 (34.1)
2	1816 (71.5)	2210 (87)	18.5 (40.7)
3	2832 (111.5)	3226 (127)	21.5 (47.3)
4	3848 (151.5)	4242 (167)	25.5 (56.1)
4021	412 (16.2)	712 (28)	10.5 (23.1)
4014	235 (9.3)	534 (21)	9.5 (20.9)

12	卡簧Permeate Retaining Ring	2	SUS304
11	挡块Stop dog	6	SUS304
10	挡圈Retaining ring	2	SUS304
09	鞍座Saddle	2-3	TPU(S60D)
07/08	钢带Strap+螺丝screwhead	2-3	A-666, 304+SUS304
06	小O型胶圈Small O-type rubber ring	2	EPDM 512
05	大O型胶圈Large O-type rubber ring	2	EPDM 512
04	密封板Sealboard	2	ABS
03	承压板Pressure plate	2	SB-209, 6061-T651
02	进、出水口钢管Intake and outlet pipe	2	2205
01	壳体Shell	1	环氧+玻纤Epoxy + glass fiber
	名称	数量	材料

SIGNATURE		
DESIGN	NAME	DATE
	陈勇	2018.1.25
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

**Winder** 河北成达华膜科技有限公司  
Hebei Chengda Huamo Technology Co., Ltd

型号 TYPE: 4寸端开1200P      单位UNIT: MM

仅供参考，零部件以图纸为准，变更不另行通知