



- 1、设计压力2.1MPa(300PSI)
Design Pressure 2.1MPa(300PSI)
- 2、设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 3、最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、净水口最大工作压力0.88Mpa(125PSI)。
The maximum operating pressure of the water purification nozzle is 0.88 MPA (125 PSI).
- 6、项目11仅在浓水端；项目3为常规1.5寸(DN40)。
Item 11 is on the water side only;
Item 3 is at regular 1.5 inches (DN40).
- 7、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	膜壳型号 Model number	S (mm)	L (mm)	P (mm)	近似重量 WEIGHT (kg)	序号	名称	数量	材料	备注
1	8040	435	1435	1120	26	1	壳体 Shell body	1	环氧玻璃钢	
2	8080	1453	2453	2136	31	2	挡块 Block block	2	合金ABS改型塑料	
3	80120	2469	3469	3152	38	3	侧口Side opening	2	304不锈钢	
4	80160	1700x2	4485	4168	44	4	侧口两圈 Side collar	2	304不锈钢	
5	80200	2250x2	5501	5184	51	5	侧口密封圈Side Ring	4	三元乙丙	41*3.1
6	80240	2700x2	6517	6200	57	6	净水堵Clean water blocking	1	ABS工程塑料	
7	80320	3250x2	7533	7216	65	7	净水堵胶圈Water cleaning rubber ring	1	三元乙丙	44*3.5
						8	密封板(300Psi)Sealing Plate	2	合金ABS改型塑料	
						9	π型密封胶圈 π Type Rubber Ring	2	硅胶	
						10	止推环Thrust ring	1	ABS工程塑料	
						11	适配器小O型胶圈ADAPTERS, small o-ring	4	硅胶	24*3
						12	适配器Adapters	2	合金ABS改型塑料	
						13	适配器大O型胶圈ADAPTOR large o-ring	4	三元乙丙	32*3
						14	鞍座Saddles(3芯以上均为3个)	2-3	软PVC	
						15	钢带Steel Strip(3芯以上均为3个)	2-3	304不锈钢+铜螺母+橡胶护套	
						16	钢带螺栓Steel Strip bolt	4-6	201不锈钢	M8*90
						序号	名称	数量	材料	备注

SIGNATURE		
	NAME	DATE
DESIGN	陈勇	2021.9.11
REVIEW		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

HANTIA 河北成达华膜科技有限公司
Hebei Chengda HuaMo Technology Co., Ltd

型号 TYPE
80S300

单位UNIT:
MM

仅供参考，零部件以图纸为准，变更不另行通知