



- 设计压力3.1MPa(450PSI)  
Design Pressure 3.1MPa(450PSI)
- 设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水  
Media:Water PH3-10
- 净水口最大工作压力0.88Mpa (125PSI)。  
The maximum operating pressure of the water purification nozzle is 0.88 MPA (125 PSI).
- 项目11仅在浓水端; 项目3为常规1.5寸(DN40)。  
Item 11 is on the water side only;  
Item 3 is at regular 1.5 inches (DN40) .
- 请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	膜壳型号 Model number	S (mm)	L (mm)	P (mm)	近似重量 WEIGHT (kg)	序号	名称	数量	材料	备注
1	8040	435	1435	1120	30	1	壳体 Shell body	1	环氧玻璃钢	
2	8080	1453	2453	2136	37	2	挡块 Block block	6	铝合金	
3	80120	2469	3469	3152	44	3	侧口Side opening	2	304不锈钢	
4	80160	1700x2	4485	4168	50	4	侧口两圈 Side collar	2	304不锈钢	
5	80200	2250x2	5501	5184	57	5	侧口密封圈Side Ring	4	三元乙丙	41*3.1
6	80240	2700x2	6517	6200	63	6	净水堵Clean water blocking	1	ABS工程塑料	
7	80320	3250x2	7533	7216	71	7	净水堵胶圈Water cleaning rubber ring	1	三元乙丙	44*3.5
						8	承压板Bearing Plate	2	铸铝	
						9	π型密封胶圈 π Type Rubber Ring	2	硅胶	
						10	密封板 (450Psi)Sealing Plate	2	合金ABS改性塑料	
						11	止推环Thrust ring	1	ABS工程塑料	
						12	适配器小O型胶圈ADAPTERS, small o-ring	4	硅胶	24*3
						13	适配器Adapters	2	合金ABS改性塑料	
						14	适配器大O型胶圈ADAPTOR large o-ring	4	三元乙丙	32*3
						15	鞍座Saddles (3芯以上均为3个)	2-3	软PVC	
						16	钢带Steel Strip (3芯以上均为3个)	2-3	304不锈钢+铜螺母+橡胶护套	
						17	钢带螺栓Steel Strip bolt	4-6	201不锈钢	M8*90
						18	定位卡簧Limit Clip	2	304不锈钢	
						序号	名称	数量	材料	备注

SIGNATURE		
	NAME	DATE
DESIGN	陈勇	2021.9.11
REVIEW		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

**HANTIA** 河北成达华膜科技有限公司  
Hebei Chengda Hualuo Technology Co., Ltd

型号 TYPE  
80S450

单位UNIT:  
MM

仅供参考, 零部件以图纸为准, 变更不另行通知