



- 1、设计压力2.1MPa(300PSI)
Design Pressure 2.1MPa(300PSI)
- 2、设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、项目3仅在浓水端;
item 3 is at the concentrated end only;
- 6、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	435	1435	1120	24
2	1453	2453	2136	30
3	2469	3469	3152	37
4	1700x2	4485	4168	43
5	2250x2	5501	5184	50
6	2700x2	6517	6200	57
7	3250x2	7533	7216	63

13/14 挡块螺丝	6	SUS304
11/12 钢带STRAP+螺丝screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
10 鞍座SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
9 侧口密封圈SIDE PORT SEAL RING	4	EPDM 512
8 侧口两圈	2	SUS304
7 侧口SIDE PORT	2	SUS304
6 π型密封胶圈π SEALING RUBBER RING	2	硅胶
5 适配器大/小型圈ADAPTOR LARGE/SMALL O GLUE	4+4	硅胶
4 适配器ADAPTOR	2	ABS
3 止推环THRUST CONE	1	工程塑料Engineering Plastic
2 承压头HEAD SEAL	2	ABS
1 壳体SHELL	1	FIBER GLASS +EPOXY
名称	数量	材料

SIGNATURE		
DESIGN	NAME	DATE
	户景伟	2022.3.12
REVIEW		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

河北成达水处理科技有限公司
Hebei Hatanga Water Technology Co., Ltd.

型号 TYPE
80S300

单位UNIT:
MM

仅供参考, 零部件以图纸为准, 变更不另行通知