



- 1、设计压力13.8MPa(2000PSI)
Design Pressure 13.8MPa(2000PSI)
- 2、设计温度66℃(150°F)
Design Temperature 66℃(150°F)
- 3、最低允许温度-10℃(14°F)
Min Temperature -10℃(14°F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、净水口压力为0.88MPa(125PSI)
0.88MPa(125PSI)
- 6、项目3数量由客户选择决定；项目5仅在浓水端
Media:Water PH3-10
- 7、图纸仅供参考，具体以实物为准
Drawings are for reference only, in kind
- 8、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	664 (26.1)	1564 (61.6)	1147 (45.2)	0
2	1680 (66.1)	2580 (101.6)	2163 (85.2)	0
3	2696 (106.1)	3596 (141.6)	3179 (125.2)	0
4	3712 (146.1)	4612 (181.6)	4195 (165.2)	0
5	4728 (186.1)	5628 (221.6)	5211 (205.2)	0
6	5744 (226.1)	6644 (261.6)	6227 (245.2)	0
7	6760 (266.1)	7660 (301.6)	7243 (285.2)	0

18	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
17	螺栓 BOLT	6	SUS304
16	定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
15	挡块 BLOCK	6	SUS304
14	嵌入钢圈 EMBEDDED RING	2	SUS304
12/13	钢带 STRAP+螺丝 screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小O型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板O型圈 SEALING PLATE O-RING	2	丁腈
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	SUS304
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
	NAME	DATE
设计	户景伟	2022.3.12
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder® 河北成达水处理科技有限公司
Hebei Chengda Water Technology Co., Ltd

型号 TYPE W80S2000	单位 UNIT: MM
仅供参考，零部件以图纸为准，变更不另行通知	