



- 1、设计压力4.1MPa(600PSI)
Design Pressure 4.1MPa(600PSI)
- 2、设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 3、最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 4、工作介质为PH3-10的水
Water working medium PH3-10
- 5、净水口压力为0.88MPa(125PSI)
Water mouth pressure 0.88 MPa(125 PSI)
- 6、项目5仅在浓水端
Item 5. At the end of concentrated water only
- 7、图纸仅供参考，具体以实物为准
Drawings are for reference only, in kind
- 8、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	736 (29)	1496 (58.9)	40 (88)
2	1752 (69)	2512 (98.9)	53 (116.6)
3	2768 (109)	3528 (138.9)	66 (145.2)
4	3784 (149)	4544 (178.9)	79 (173.8)
5	4800 (189)	5560 (218.9)	92 (202.4)
6	5816 (229)	6576 (258.9)	105 (231)
7	6832 (269)	7592 (298.9)	118 (259.6)

17	紧固螺母 FASTENING NUT	2	工程塑料Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
14	嵌入钢圈 EMBEDDED RING	2	SUS304
12/13	钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板O型胶圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料Engineering Plastic
04	两圈挡环 TWO RINGS	4	SUS304
03	密封胶圈 SEALED RUBBER RINGS	4	EPDM 512
02	进、出水口 ACCESS TO WATER	2	SUS316L
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
设计	户景伟	2022.3.12
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder®		河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
型号 TYPE	W80E600	单位 UNIT:	MM
仅供参考，零部件以图纸为准，变更不另行通知			