

技术要求:

- 膜壳最大压力为: 450PSI (31KG/CM²),
水介质温度: 1℃~49℃;
不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 450PSI, (31KG/CM²)


Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

侧口		1"		
名称		规格		
长度编码 Length Code	L Inch (mm)	P Standard Inch (mm)	S Inch (mm)	壳体 重量 lb (kg)
1	46.4 (1178)	39.6 (1006)	22.7 (578)	20 (9)
2	86.4 (2194)	79.6 (2022)	62.7 (1594)	26 (12)
3	126.4 (3210)	119.6 (3038)	102.7 (2610)	35 (16)
4	166.4 (4226)	159.6 (4054)	142.8 (3626)	38 (19)

11	月牙片Crescent film	4	SA-213, 304
10	内六角螺栓Inner hexagonal head bolt	4	M6*1
9	钢带护套Steel sheath	2-3	软质PVC Soft PVC
8	钢带螺母Steel strip nut	4-6	HPB59-1
7	承压头0型圈Pressure head 0 type ring	2	EPDM
6	大密封圈Large sealing ring	2	EPDM
5	侧口Side entrance	2	304/316L
4	侧口螺母Side nut	2	304/316L
3	侧口密封圈Side screw sealing ring	2	EPDM
2	承压头Pressure head	2	ABS
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

	NAME	DATE	 河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	卢景伟	2022.3.12		
审核				
审批			型号 TYPE	单位UNIT:
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			40S450	MM
			仅供参考, 零部件以图纸为准, 变更不另行通知	