


- 设计压力8.3MPa(1200PSI)
Design Pressure 8.3MPa(1200PSI)
- 设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 工作介质为PH3-10的水
Media:Water PH3-10
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

| 长度编码 Length | S (mm) | L (mm) | P (mm) | 重量 WEIGHT (kg) | 名称 | 数量 | 材料 |
|----------------|-----------------|-----------------|-----------------|----------------------|----------------------------------|-----|--------------------------|
| 1 | 624 (24.6) | 1234 (48.6) | 1013 (39.9) | 18 (39.6) | 13 卡簧Permeate Rrtaining Ring | 2 | SUS304 |
| | | | | | 12 挡块Stop dog | 6 | SS316L |
| | | | | | 11 挡圈Retaining ring | 2 | SS316L |
| | | | | | 10 鞍座Saddle | 2-3 | TPU(S60D) |
| 2 | 1640 (64.6) | 2250 (88.6) | 2029 (79.9) | 23 (50.6) | 08/09 钢带Strap+螺丝screwhead | 2-3 | A-666,304+SUS304 |
| | | | | | 07 密封板Sealboard | 2 | ABS |
| | | | | | 06 承压板Pressure plate | 2 | SB-209,6061-T651 |
| | | | | | 05 大O型胶圈Large O-type rubber ring | 2 | EPDM 512 |
| 3 | 2656 (104.6) | 3266 (128.6) | 3045 (119.9) | 28 (61.6) | 04 侧口密封圈Side screw sealing ring | 2 | EPDM 512 |
| | | | | | 03 侧口螺母Side nut | 2 | SUS304 |
| | | | | | 02 侧口Side entrance | 2 | SS316L |
| 4 | 3672 (144.6) | 4282 (168.6) | 4061 (159.9) | 33 (72.6) | 01 壳体Shell | 1 | 环氧+玻纤Epoxy + glass fiber |

| SIGNATURE | | |
|--|------|-----------|
| DESIGN | NAME | DATE |
| | 户景伟 | 2022.3.12 |
| THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY | | |


 河北成达水处理科技有限公司
 Hebei Chengda Water Technology Co., Ltd.

| | |
|-------------------------|---------|
| 型号 TYPE | 单位UNIT: |
| 4寸侧开1200P | MM |
| 仅供参考, 零部件以图纸为准, 变更不另行通知 | |