



技术要求:

1. 膜壳最大压力为: 450PSI (3.1Mpa);
2. 工作介质温度: -10℃~49℃;
3. 工作介质用于苦咸水或海水, PH:3~11;

Technical Requirements:

1. The maximum pressure of Membrane Shell is: 450 PSI (3.1 MPA) ;
2. Working medium temperature:-10 ° C ~ 49 ° C;
3. The working medium is used for brackish water or seawater, Ph: 3 ~ 11

10	紧固螺栓Fastening Bolt	4	304	
9	挡片Baffle sheet	4	304	
8	捆带螺栓Strap Bolt	4	304	M8*70螺杆
7	鞍座Saddles	2	橡胶	
6	捆带Strapping	2	304不锈钢	
5	净水堵Clean water blocking	1	工程塑料	
4	密封板小O型圈Seal Plate small o-ring	2	三元乙丙	19*2.65
3	密封板大O型圈Seal Plate large o-ring	2	三元乙丙	100*6
2	密封板Sealing Plate	2	ABS	
1	壳体Shell body	1	FRP	
序号	名称	数量	材料	备注

长度编码 Length	L (mm)	S (mm)	近似重量 Weight (kg)
4021	653	500	5
1	1135	635	8
2	2151	1651	12
3	3167	2667	16.5
4	4183	1840x2	20.5

	NAME	DATE	Winder® 河北水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	户景伟	2022. 3. 12	型号 TYPE	单位UNIT:
审核			40E450	MM
审批			仅供参考, 零部件以图纸为准, 变更不另行通知	
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY				