



技术要求:

1. 膜壳最大压力为: 300PSI (21KG/CM<sup>2</sup>),

水介质温度: 1℃~49℃;

不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 300PSI, (21KG/CM<sup>2</sup>)

Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

10	鞍座Saddle	2	TPU(S60D)
9	钢带Steel strip	2	A666, 304
8	钢带螺母Steel strip nut	4	HPB59-1
7	内六角螺栓Inner hexagonal head bolt	4	M5*1.5, 304
6	月牙片Crescent film	4	SA-213, 304
5	膜密封圈Film sealing ring	4	EPDM
4	大密封圈Large sealing ring	2	EPDM
3	膜壳标签Shell label	1	不干胶标签Self-adhesive label
2	承压头Pressure head	2	PP+30%PG
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

SIGNATURE			河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	户景伟	2022. 3. 12		
审核				
审批			型号 TYPE	单位UNIT:
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			W25E300	MM
			仅供参考, 零部件以图纸为准, 变更不另行通知	