



技术要求:

1、膜壳最大压力为: 1000PSI (69KG/CM<sup>2</sup>),

2、水介质温度: 1℃~49℃;

不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 1000PSI, (69KG/CM<sup>2</sup>)

Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

10	鞍座Saddle	2	TPU(S60D)
9	钢带Steel strip	2	A666, 304
8	钢带螺母Steel strip nut	4	HPB59-1
7	内六角螺栓Inner hexagonal head bolt	4	M5*1.5, 304
6	月牙片Crescent film	4	SA-213, 304
5	膜密封圈Film sealing ring	4	EPDM
4	大密封圈Large sealing ring	2	EPDM
3	膜壳标签Shell label	1	不干胶标签Self-adhesive label
2	承压头Pressure head	2	2205
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

SIGNATURE			Winder® 河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	户景伟	2022. 3. 12	型号 TYPE	单位UNIT:
审核			W25E1000	MM
审批			仅供参考, 零部件以图纸为准, 变更不另行通知	
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY				

长度编码 Length Code	L Inch (mm)	S Span (mm)	A Span (mm)	壳体重量 lb (kg)
25/14	19.09 (485)	16.72 (425)	11.2 (285)	5.5 (2.5)
25/21	26.06 (662)	23.72 (602)	18.3 (462)	7.5 (3.4)
25/40	45.08 (1145)	42.72 (1085)	29.3 (745)	14.5 (6.6)