



膜壳型号 Model NO.	L (MM)	S (MM)
GL80-150-20	814	300
GL80-150-40	1305	600
GL80-150-60	1814	1105

序号 NO.	名称 Name	材料 Material	数量 QTY	备注
1	壳体 shell	环氧玻璃钢	1	
2	挡块 Block block	合金ABS改性塑料	6	
3	进水端板 inlet sealing plate	合金ABS改性塑料	1	
4	止推环 thrust cone	合金ABS改性塑料	1	
5	密封圈 sealing ring	硅胶	2	
6	出水端板 outlet sealing plate	合金ABS改性塑料	1	
7	捆带 strap	304不锈钢-橡胶	2	
8	捆带螺栓 strap nut	A216	4	M8×90
9	鞍座 saddle	软PVC	2	

- 设计压力1.0MPa(10KG)
Design Pressure 1.0MPa(10KG)
- 设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 工作介质为PH3-10的水
Media: Water PH3-10
- 请按照说明书正确使用
Please operate it according to operation manual

	NAME	DATE
设计	户景伟	2022. 3. 12
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
型号 TYPE GL80E-E150	单位 UNIT: MM
仅供参考, 零部件以图纸为准, 变更不另行通知	