



- 1、设计压力10.4MPa(1500PSI)
Design Pressure 10.4MPa(1500PSI)
- 2、设计温度66℃(150°F)
Design Temperature 66℃(150°F)
- 3、最低允许温度-10℃(14°F)
Min Temperature -10℃(14°F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、净水口压力为0.88MPa(125PSI)
0.88MPa(125PSI)
- 6、项目3数量由客户选择决定;项目5仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 7、图纸仅供参考,具体以实物为准
Drawings are for reference only, in kind
- 8、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)
1	654 (25.7)	1554 (61.2)	1147 (45.2)
2	1670 (65.7)	2570 (101.2)	2163 (85.2)
3	2686 (105.7)	3586 (141.2)	3179 (125.2)
4	3702 (145.7)	4602 (181.2)	4195 (165.2)
5	4718 (185.7)	5618 (221.2)	5211 (205.2)
6	5734 (225.7)	6634 (261.2)	6227 (245.2)
7	6750 (265.7)	7650 (301.2)	7243 (285.2)

18	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
17	螺栓 BOLT	6	SUS304
16	定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
15	挡块 BLOCK	6	SUS316L
14	嵌入钢圈 EMBEDDED RING	2	SUS316L
12/13	钢带 STRAP+螺丝 screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板 O型圈 SEALING PLATE O-RING	2	丁腈
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	SUS316L
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
	NAME	DATE
设计	户景伟	2022.3.12
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder® 河北成达水处理科技有限公司
Hebei Chengda Water Technology Co., Ltd

型号 TYPE W80S1500	单位 UNIT: MM
仅供参考, 零部件以图纸为准, 变更不另行通知	