


- 1、设计压力2.1MPa(300PSI)
Design Pressure 2.1MPa(300PSI)
- 2、设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 3、最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 4、工作介质为PH3-10的水
Water working medium PH3-10
- 5、净水口压力为0.88MPa(125PSI)
Water mouth pressure 0.88 MPa(125 PSI)
- 6、项目5仅在浓水端
Item 5. At the end of concentrated water only
- 7、图纸仅供参考，具体以实物为准
Drawings are for reference only, in kind
- 8、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	690 (27.2)	1450 (57)	30 (66)
2	1706 (67.2)	2466 (97)	40.5 (89.1)
3	2722 (107.2)	3482 (137)	51 (112.2)
4	3738 (147.2)	4498 (177)	61.5 (135.3)
5	4754 (187.2)	5514 (217)	72 (158.4)
6	5770 (227.2)	6530 (257)	82.5 (181.5)
7	6786 (267.2)	7546 (297)	93 (204.6)

17	紧固螺母 FASTENING NUT	2	工程塑料Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
14	适配器大O型圈ADAPTOR LARGE O GLUE	4	EPDM 512
12/13	钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器ADAPTOR	2	ABS
08	适配器小O型圈ADAPTOR SMALL O GLUE	4	硅胶
07	密封板O型圈SEALING PLATE O-RING	2	EPDM 512
06	承载板BEARING PLATE	2	SB-209, 6061-T651
05	止推环THRUST CONE	1	工程塑料Engineering Plastic
04	两圈挡环TWO RINGS	2	SUS304
03	密封胶圈SEALED RUBBER RINGS	4	EPDM 512
02	进、出水口ACCESS TO WATER	2	SUS304
01	壳体SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
设计	户景伟	2022. 3. 12
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

		河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
型号 TYPE	W80E300	单位UNIT:	MM
仅供参考，零部件以图纸为准，变更不另行通知			