

技术要求:

- 膜壳最大压力为: 300PSI (21KG/CM²),
水介质温度: 1℃~49℃;
不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 300PSI, (21KG/CM²)


Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

11	月牙片Crescent film	4	SA-213, 304
10	内六角螺栓Inner hexagonal head bolt	4	M6*1, 304
9	钢带护套Steel sheath	2-3	软质PVC Soft PVC
8	钢带螺母Steel strip nut	4-6	HPB59-1
7	承压头O型圈Pressure head O type ring	2	EPDM
6	大密封圈Large sealing ring	2	硅胶
5	侧口Side entrance	2	304/316L
4	侧口螺母Side nut	2	304/316L
3	侧口密封圈Side screw sealing ring	2	EPDM
2	承压头Pressure head	2	ABS
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

侧口		1"		
名称		规格		
长度编码 Length Code	L Inch (mm)	P Standard Inch (mm)	S Inch (mm)	壳体 重量 lb (kg)
1	46.4 (1178)	39.6 (1006)	22.7 (578)	17 (8)
2	86.4 (2194)	79.6 (2022)	62.7 (1594)	25 (11)
3	126.4 (3210)	119.6 (3038)	102.7 (2610)	33 (15)
4	166.4 (4226)	159.6 (4054)	142.8 (3626)	40 (18)

	NAME	DATE	 河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	户景伟	2022. 3. 12		
审核				
审批				
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			型号 TYPE	单位UNIT:
			40S300	MM
仅供参考, 零部件以图纸为准, 变更不另行通知				