



- 设计压力6.9MPa(1000PSI)
Design Pressure 6.9MPa(1000PSI)
- 设计温度66℃(150° F)
Design Temperature 66℃(150° F)
- 最低允许温度-10℃(14° F)
Min Temperature -10℃(14° F)
- 工作介质为PH3-10的水
Media:Water PH3-10
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)	名称	数量	材料
1	624 (24.6)	1224 (48.6)	1013 (39.9)	13 (28.6)	13	2	SUS304
					12	6	SS316L
					11	2	SS316L
					10	2-3	TPU(S60D)
2	1640 (64.6)	2240 (88.6)	2029 (79.9)	16 (35.2)	08/09	2-3	A-666,304+SUS304
					07	2	ABS
					06	2	SB-209,6061-T651
					05	2	EPDM 512
3	2656 (104.6)	3256 (128.6)	3045 (119.9)	19 (41.8)	04	2	EPDM 512
					03	2	SUS304
					02	2	SS316L
					01	1	环氧+玻纤Epoxy + glass fiber
4	3672 (144.6)	4272 (168.6)	4061 (159.9)	22 (48.4)	名称	数量	材料

SIGNATURE		
DESIGN	NAME	DATE
	户景伟	2022.3.12
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		


 河北成达水处理科技有限公司
 Hebei Chengda Water Technology Co., Ltd.

型号 TYPE	单位UNIT:
4寸侧开600P	MM
仅供参考, 零部件以图纸为准, 变更不另行通知	