



	2. 1/2''-8NPSM Internal thread
Medium Dia	2.762-2.768"
Small Dia	2.705-2.715"
Large Dia	2.843-2.849"

Remark  
 1. Product type identification see outer packaging logo.  
 2. The product color is consistent with the color of the tape packaging box.

Technical Parameters

Model	Opening Size	VOL (Ltrs.)	Size Parameters (mm)								Base	Weight (kg)
			D1	H1	H2	F	WA	WLB	WB	WLA		
9×13	2.5''T	11.2	231	346	180	50	5	2	5	1	none	1.7±0.2
9×17	2.5''T	13.8	231	443	275	50	5	2	5	1	none	2.0±0.2
9×35	2.5''T	31.1	231	888	720	100	5	2	5	1	none	3.3±0.3
9×42	2.5''T	37.8	231	1061	893	100	5	2	5	1	none	4.2±0.4
9×48	2.5''T	43.7	231	1213	1045	100	5	2	5	1	none	4.7±0.4

Note:  
 1. The vacuum valve must be installed on the device.  
 2. Operation Instructions:  
 A. Max working pressure: 10.5Bar (150Psi)  
 B. Temperature Range: 1-50°C (34-127°F)  
 C. Maximum vacuum: 17Kpa (5''Hg)

Sign			Hebei Chengda WaterTechnology Co.,Ltd.			
	Signature	Date	Material:	FRP	Projection:	
Designer	Chengyang Sun	2024.7.16	Model:	9" 2.5''T	Name:	FRP tank
Review	Jingwei Hu	2024.7.18	Version number:	00	Description of Change Version	Drawing No. CD-22-09-28/16
Approve			Please don't measure the size of the drawing		Unit: mm	1 Page Page 1