



2. 1/2"-8NPSM Internal thread	
Medium Dia	2.762-2.768"
Small Dia	2.705-2.715"
Large Dia	2.843-2.849"

Remark
 1. Product type identification see outer packaging logo.
 2. The product color is consistent with the color of the tape packaging box.

Technical Parameters												
Model	Opening Size	VOL (Ltrs.)	Size Parameters (mm)								Base	Weight (kg)
			D1	H1	H2	F	WA	WLB	WB	WLA		
610	T 2.5 "	3.2	156	254	161	10	5	2	4	1	none	0.8±0.1
613	T 2.5 "	4.7	156	341	247	10	5	2	4	1	none	1.1±0.1
617	T 2.5 "	6.5	156	432	339	50	5	2	4	1	none	1.4±0.2
618	T 2.5 "	7.0	156	459	364	50	5	2	4	1	none	1.4±0.2
629	T 2.5 "	12.0	156	736	643	100	5	2	4	1	none	1.9±0.2
635	T 2.5 "	14.8	156	889	796	100	5	2	4	1	none	2.1±0.3

Note:

- The vacuum valve must be installed on the device.
- Operation Instructions:
 - Max working pressure: 8bar(125Psi)
 - Temperature Range:1-50°C (34-127°F)
 - Maximum vacuum:17Kpa (5"Hg)

Sign			Hebei Chengda WaterTechnology Co.,Ltd.			
	Signature	Date	Material:	FRP	Projection:	
Designer	Chengyang Sun	2024. 07. 18	Model:	6", 2.5"T	Name:	FRP tank
Review	Jingwei Hu	2024. 07. 18	Version number:00	Description of Change Version	Drawing No.	CD-22-09-27/02
Approve			Please don't measure the size of the drawing		Unit: mm	1 Page Page 1