



- 设计压力2.1MPa (300PSI)
Design Pressure 2.1MPa (300PSI)
- 设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水
Media: Water PH3-10
- 项目10仅在原水端; 项目5仅在浓水端;
Item 10 is at the RAW end only; item 5 is at the concentrated end only; item 3 is at the conventional 1.5 inch.
项目3为常规1.5寸。
Please operate it according to operation manual

| 长度编码 Length | S (mm) | L (mm) | P (mm) | 重量 WEIGHT (kg) | 名称 | 数量 | 材料 |
|----------------|-----------|-----------|-----------|----------------------|---|-----|-------------------------|
| 1 | 715 | 1435 | 1120 | 30 | 18 垫片 shim block | 3 | 工程塑料Engineering Plastic |
| 2 | 1731 | 2453 | 2136 | 37 | 17 卡簧 PERMEATE RETAINING RING | 2 | SUS304 |
| 3 | 2747 | 3469 | 3152 | 44 | 15/16 钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90) | 2-3 | A-666, 304+A216 |
| 4 | 3763 | 4485 | 4168 | 51 | 14 鞍座SADDLE (3芯以上均为3个) | 2-3 | TPU (S60D) |
| 5 | 4779 | 5501 | 5184 | 58 | 13 挡块螺丝 BAFFLE FIXING BOLTS | 6 | SUS304 |
| 6 | 5795 | 6517 | 6200 | 65 | 12 挡块 LINK STOPPER | 6 | 铝合金 |
| 7 | 6811 | 7533 | 7216 | 72 | 11 承压头 (300Psi) HEAD SEAL | 2 | ABS |
| | | | | | 10 适配器ADAPTOR | 2 | ABS |
| | | | | | 08/09 适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUB | 4+4 | EPDM512+硅胶 |
| | | | | | 07 π型密封胶圈 π SEALING RUBBER RING | 2 | 硅胶 |
| | | | | | 06 承载板BBARING PLATE | 2 | 铸铝 |
| | | | | | 05 止推环THRUST CONE | 1 | 工程塑料Engineering Plastic |
| | | | | | 04 侧口两圈 SIDE DORT | 2 | SUS304 |
| | | | | | 03 侧口SIDE PORT | 2 | 304不锈钢 |
| | | | | | 02 侧口密封胶圈SIDE PORT SEAL RING | 4 | EPDM 512 |
| | | | | | 01 壳体SHELL | 1 | FIBER GLASS +EPOXY |

| | NAME | DATE | Winder-G 河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd | |
|--|------|------------|---|---------|
| 设计 | 卢景伟 | 2022.11.27 | 型号 TYPE | 单位UNIT: |
| 审核 | | | G80S300 | MM |
| 审批 | | | 仅供参考, 零部件以图纸为准, 变更不另行通知 | |
| THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY | | | | |