



- 设计压力2.1MPa (300PSI)
Design Pressure 2.1MPa (300PSI)
- 设计温度66°C (150° F)
Design Temperature 66°C (150° F)
- 最低允许温度-10°C (14° F)
Min Temperature -10°C (14° F)
- 工作介质为PH3-10的水
Media: Water PH3-10
- 净水口压力为0.88MPa (125PSI)
0.88MPa (125PSI)
- 项目3数量由客户选择决定; 项目5仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	681 (26.8)	1441 (56.7)	1127 (44.4)	35 (77)
2	1697 (66.8)	2457 (96.7)	2143 (84.4)	45.5 (100.1)
3	2713 (106.8)	3473 (136.7)	3159 (124.4)	56 (123.2)
4	3729 (146.8)	4489 (176.7)	4175 (164.4)	66.5 (146.3)
5	4745 (186.8)	5505 (216.7)	5191 (204.4)	77 (169.4)
6	5761 (226.8)	6521 (256.7)	6207 (244.4)	87.5 (192.5)
7	6777 (266.8)	7537 (296.7)	7223 (284.4)	98 (215.6)

18	垫片 shim block	3	工程塑料Engineering Plastic
17	紧固螺母 FASTENING NUT	2	工程塑料Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
13/14	钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
12	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
11	密封板 SEALBOARD	2	ABS
10	适配器 ADAPTOR	2	ABS
09	适配器小O型圈 ADAPTOR SMALL O GLUE	4	硅胶 SILICON RUBBER
08	适配器大O型圈 ADAPTOR LARGE O GLUE	4	EPDM 512
07	密封板O型圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT NUTS	2-4	SUS304
03	侧口 SIDE PORT (3")	2-4	316L 不锈钢 AISI316
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
	NAME	DATE
设计	卢景伟	2022.12.27
审核		
审批		

Winder 河北成达水处理科技有限公司
Hebei Chengda Water Technology Co., Ltd

型号 TYPE W80S300-3"	单位 UNIT: MM
------------------------------	-----------------------

仅供参考, 零部件以图纸为准, 变更不另行通知

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY