



- 设计压力4.1MPa (600PSI)  
Design Pressure 4.1MPa (600PSI)
- 设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水  
Media: Water PH3-10
- 净水口压力为0.88MPa (125PSI)  
0.88MPa (125PSI)
- 项目3数量由客户选择决定; 项目5仅在浓水端  
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考, 具体以实物为准  
Drawings are for reference only, in kind
- 请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	698 (27.5)	1478 (58.2)	1127 (44.4)	45 (99)
2	1714 (67.5)	2494 (98.2)	2143 (84.4)	58 (127.6)
3	2730 (107.5)	3510 (138.2)	3159 (124.4)	71 (156.2)
4	3746 (147.5)	4526 (178.2)	4175 (164.4)	84 (184.8)
5	4762 (187.5)	5542 (218.2)	5191 (204.4)	97 (213.4)
6	5778 (227.5)	6558 (258.2)	6207 (244.4)	110 (242)
7	6794 (267.5)	7574 (298.2)	7223 (284.4)	123 (270.6)

18	垫片 shim block	3	工程塑料Engineering Plastic
17	紧固螺母 FASTENING NUT	2	工程塑料Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
14	嵌入钢圈 EMBEDDED RING	2	SUS304
12/13	钢带 STRAP+螺丝 SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小 O型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板 O型圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	316L 不锈钢 AISI316
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
	NAME	DATE
设计	卢景伟	2022.12.27
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

**Winder** 河北成达水处理科技有限公司  
HobeI Chengda Water Technology Co., Ltd

型号 TYPE	单位 UNIT:
W80S600	MM
仅供参考, 零部件以图纸为准, 变更不另行通知	