



- 设计压力 8.3MPa (1200PSI)
Design Pressure 8.3MPa (1200PSI)
- 设计温度 66°C (150°F)
Design Temperature 66°C (150°F)
- 最低允许温度 -10°C (14°F)
Min Temperature -10°C (14°F)
- 工作介质为 PH3-10 的水
Media: Water PH3-10
- 净水口压力为 0.88MPa (12.5PSI)
0.88MPa (12.5PSI)
- 项目 3 数量由客户选择决定; 项目 5 仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)	19 垫片 shim block	3 工程塑料 Engineering Plastic
1	646 (25.4)	1546 (60.8)	1127 (44.4)	70 (154)	18 紧固螺母 FASTENING NUT	2 工程塑料 Engineering Plastic
2	1662 (65.4)	2562 (100.8)	2143 (84.4)	89 (195.8)	17 螺栓 BOLT	6 SUS304
3	2678 (105.4)	3578 (140.8)	3159 (124.4)	108 (237.6)	16 定位环 POSITIONING RING	2 工程塑料 Engineering Plastic
4	3694 (145.4)	4594 (180.8)	4175 (164.4)	127 (279.4)	15 挡块 BLOCK	6 SUS316L
5	4710 (185.4)	5610 (220.8)	5191 (204.4)	146 (321.2)	14 嵌入钢圈 EMBEDDED RING	2 SUS316L
6	5726 (225.4)	6626 (260.8)	6207 (244.4)	165 (363)	12/13 钢带 STRAP+螺丝 screwhead (螺栓尺寸: M8*90)	2-3 A-666, 304+A216
7	6742 (265.4)	7642 (300.8)	7223 (284.4)	184 (404.8)	11 鞍座 SADDLE (3芯以上均为3个)	2-3 TPU(S60D)
					10 密封板 SEALBOARD	2 ABS
					09 适配器 ADAPTOR	2 ABS
					08 适配器大/小型圈 ADAPTOR LARGE/SMALL O GLUE	4+4 三元乙丙 EPDM
					07 密封板 O型圈 SEALING PLATE O-RING	2 丁腈 NBR
					06 承载板 BEARING PLATE	2 SB-209, 6061-T651
					05 止推环 THRUST CONE	1 工程塑料 Engineering Plastic
					04 侧口螺母 SIDE DORT NUTS	2-4 SUS304
					03 侧口 SIDE PORT	2-4 超级双相钢 Super duplex SS2507
					02 侧口密封圈 SIDE PORT SEAL RING	4 EPDM 512
					01 壳体 SHELL	1 FIBER GLASS +EPOXY
					名称	数量 材料

SIGNATURE			河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
	NAME	DATE		
设计	卢景伟	2022.12.27		
审核				
审批			型号 TYPE	单位 UNIT:
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			W80S1200-3"	MM
			仅供参考, 零部件以图纸为准, 变更不另行通知	